

SECTION 1) CHEMICAL PRODUCT AND MANUFACTURER'S IDENTIFICATION

Product ID: MIRA 720PW
Product Name: MIRAVAR CV PRIMER - WHITE
Revision Date: Jan 31, 2024 **Date Printed:** Jan 31, 2024
Version: 5.0 **Supersedes Date:** Sep 10, 2019
Manufacturer's Name: Repolite Paints, Inc.
Address: 473 West 17th Street Holland, MI, US, 49423
Emergency Phone: 800-535-5053
Information Phone Number: 616-396-1275
Fax: 616-396-9654

SECTION 2) HAZARDS IDENTIFICATION

Classification

Flammable Liquids - Category 2
Acute toxicity Dermal - Category 3
Acute toxicity Inhalation Vapor - Category 3
Acute toxicity Oral - Category 3
Carcinogenicity - Category 2
Eye Irritation - Category 2A
Reproductive Toxicity - Category 2
Skin Irritation - Category 2
Specific Target Organ Toxicity - Repeated Exposure - Category 2
Specific Target Organ Toxicity - Single Exposure - Category 1
Acute aquatic toxicity - Category 3
Chronic aquatic toxicity - Category 3

Safety data sheet prepared in accordance to the United States Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200) and the Canadian Workplace Hazardous Materials Information System (WHMIS).

Pictograms



Signal Word

Danger

Hazardous Statements - Physical

H225 - Highly flammable liquid and vapor

Hazardous Statements - Health

H311 - Toxic in contact with skin

H331 - Toxic if inhaled
H301 - Toxic if swallowed
H351 - Suspected of causing cancer.
H319 - Causes serious eye irritation
H361 - Suspected of damaging fertility or the unborn child
H315 - Causes skin irritation
H373 - May cause damage to organs through prolonged or repeated exposure.
H370 - Causes damage to organs

Hazardous Statements - Environmental

H412 - Harmful to aquatic life with long lasting effects

Precautionary Statements - General

P101 - If medical advice is needed, have product container or label at hand.
P102 - Keep out of reach of children.
P103 - Read label before use.

Precautionary Statements - Prevention

P273 - Avoid release to the environment.
P280 - Wear protective gloves,protective clothing,eye protection/face protection.
P271 - Use only outdoors or in a well-ventilated area.
P264 - Wash thoroughly after handling.
P270 - Do not eat, drink or smoke when using this product.
P201 - Obtain special instructions before use.
P202 - Do not handle until all safety precautions have been read and understood.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 - Keep container tightly closed.
P240 - Ground/bond container and receiving equipment.
P241 - Use explosion-proof electrical/ventilating/lighting equipment.
P242 - Use only non-sparking tools.
P243 - Take action to prevent static discharges.
P260 - Do not breathe dust/fume/gas/mist/vapors/spray.

Precautionary Statements - Response

P302 + P352 - IF ON SKIN: Wash with plenty of water.
P312 - Call a POISON CENTER/doctor if you feel unwell.
P321 - For specific treatment see section 4.
P361 + P364 - Take off immediately all contaminated clothing. And wash it before reuse.
P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor.
P330 - Rinse mouth.
P308 + P313 - IF exposed or concerned: Get medical advice/attention.
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313 - If eye irritation persists: Get medical advice/attention.
P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P370 + P378 - In case of fire: Use dry chemical, foam, or carbon dioxide to extinguish.
P332 + P313 - If skin irritation occurs: Get medical advice/attention.
P314 - Get Medical advice/attention if you feel unwell.

P308 + P311 - IF exposed or concerned: Call a POISON CENTER/doctor.

Precautionary Statements - Storage

P405 - Store locked up.

P403 + P233 - Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 - Store in a well-ventilated place. Keep cool.

Precautionary Statements - Disposal

P501 - Dispose of contents/container to disposal recycling center. Under RCRA it is the responsibility of the user of the product to determine at the time of disposal whether the product meets RCRA criteria for hazardous waste. Waste management should be in full compliance with federal, state and local laws.

Acute toxicity of 18.9% of the mixture is unknown

SECTION 3) COMPOSITION/INFORMATION ON INGREDIENTS

CAS	Chemical Name	% By Weight
0013463-67-7	TITANIUM DIOXIDE	17% - 28%
0000067-56-1	METHANOL	11% - 26%
0001330-20-7	XYLENE	5% - 11%
0068002-19-7	Urea, polymer with formaldehyde, butylated	4% - 10%
0000123-86-4	BUTYL ACETATE	3% - 8%
0000067-64-1	ACETONE	3% - 7%
0112926-00-8	SILICA - PRECIPITATED	1.6% - 4%
0009004-36-8	CELLULOSE ACETATE BUTYRATE	1.4% - 3%
0000108-65-6	PROPYLENE GLYCOL MONOMETHYL ETHER ACETATE	1.3% - 3%
0007631-86-9	SILICA, AMORPHOUS	0.2% - 4%
0000100-41-4	ETHYLBENZENE	0.2% - 4%
0021645-51-2	ALUMINUM HYDROXIDE	0.1% - 2%
0001314-23-4	ZIRCONIA OXIDE	0.0% - 0.5%
0000071-36-3	N-BUTYL ALCOHOL	0.0% - 0.4%
0009002-88-4	POLYETHYLENE	0.0% - 0.4%
0025265-71-8	DIPROPYLENE GLYCOL	Trace
0008052-41-3	STODDARD SOLVENT	Trace
0000050-00-0	FORMALDEHYDE	Trace
0070657-70-4	2-METHOXY-1-PROPANOL ACETATE	Trace

Specific chemical identity and/or exact percentage (concentration) of the composition has been withheld to protect confidentiality.

SECTION 4) FIRST-AID MEASURES

Inhalation

Remove source of exposure or move person to fresh air and keep comfortable for breathing.

If exposed or unwell : Call a POISON CENTER/doctor

Skin Contact

Take off immediately contaminated clothing. Rinse skin with water/shower and mild soap for 5 minutes or until product is removed. Store contaminated clothing under water and wash before re-use or discard.

Eye Contact

Rinse eyes cautiously with lukewarm, gently flowing water for several minutes, while holding the eyelids open. Remove contact lenses, if present and easy to do. Continue rinsing for 15-20 minutes. Take care not to rinse contaminated water into the unaffected eye or onto the face. If eye irritation persists: Get medical advice/attention.

Ingestion

Rinse mouth. If you feel unwell or are concerned : Get medical advice/attention.

Most important symptoms and effects, both acute and delayed

No data available.

Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5) FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Dry chemical, foam, or carbon dioxide is recommended. Water spray is recommended to cool or protect exposed materials or structures. Carbon dioxide can displace oxygen. Use caution when applying carbon dioxide in confined spaces. Simultaneous use of foam and water on the same surface is to be avoided as water destroys the foam.

Unsuitable Extinguishing Media

No data available.

Specific Hazards in Case of Fire

Vapors are heavier than air and may travel along the ground to ignition sources at locations distant from material handling point.

Vapor accumulations and spray mist may flash or explode if ignited.

Closed containers may rupture due to pressure buildup when exposed to extreme heat.

Dried solids can burn.

Fire-fighting Procedures

Isolate immediate hazard area and keep unauthorized personnel out. Stop spill/release if it can be done safely. Move undamaged containers from immediate hazard area if it can be done safely. Water spray may be useful in minimizing or dispersing vapors and to protect personnel. Water may be ineffective but can be used to cool containers exposed to heat or flame. Caution should be exercised when using water or foam as frothing may occur, especially if sprayed into containers of hot, burning liquid.

Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

Special Protective Actions

Wear protective pressure self-contained breathing apparatus (SCBA) and full turnout gear.

SECTION 6) ACCIDENTAL RELEASE MEASURES

Emergency Procedure

ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).

Do not touch or walk through spilled material.

Isolate hazard area and keep unnecessary people away. Remove all possible sources of ignition in the surrounding area. Notify authorities if any exposure to the general public or the environment occurs or is likely to occur.

If spilled material is cleaned up using a regulated solvent, the resulting waste mixture may be regulated.

Recommended Equipment

Positive pressure, full-face piece self-contained breathing apparatus (SCBA), or positive pressure supplied air respirator with escape SCBA (NIOSH approved).

Personal Precautions

Avoid breathing vapor. Avoid contact with skin, eye or clothing. Do not touch damaged containers or spilled materials unless wearing appropriate protective clothing.

Environmental Precautions

Stop spill/release if it can be done safely. Prevent spilled material from entering sewers, storm drains, other unauthorized drainage systems and natural waterways by using sand, earth, or other appropriate barriers.

Methods and Materials for Containment and Cleaning up

Absorb spill with inert absorbent.

Dike area to contain spill.

SECTION 7) HANDLING AND STORAGE

Ventilation Requirements

Use only with adequate ventilation to control air contaminants to their exposure limits. The use of local ventilation is recommended to control emissions near the source.

Storage Room Requirements

Keep container(s) tightly closed and properly labeled. Store in cool, dry, well-ventilated areas away from heat, direct sunlight, strong oxidizers and any incompatibilities. Store in approved containers and protect against physical damage. Keep containers securely sealed when not in use. Indoor storage should meet OSHA standards and appropriate fire codes. Containers that have been opened must be carefully resealed to prevent leakage. Empty containers retain residue and may be dangerous. Use non-sparking ventilation systems, approved explosion-proof equipment and intrinsically safe electrical systems in areas where this product is used and stored.

Ground and bond containers and receiving equipment. Avoid static electricity by grounding.

General

Wash hands after use.

Do not get in eyes, on skin or on clothing.

Do not breathe vapors or mists.

Use good personal hygiene practices.

Eating, drinking and smoking in work areas is prohibited.

Remove contaminated clothing and protective equipment before entering eating areas.

Eyewash stations and showers should be available in areas where this material is used and stored.

SECTION 8) EXPOSURE CONTROLS/PERSONAL PROTECTION

Respiratory protection

If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker, a respiratory protection program that meets or is equivalent to OSHA 29 CFR 1910.134 and ANSI Z88.2 should be followed. Check with respiratory protective equipment suppliers.

Eye protection

Wear eye protection with side shields or goggles. Wear indirect-vent, impact and splash resistant goggles when working with liquids. If additional protection is needed for entire face, use in combination with a face shield.

Skin Protection

Use of gloves approved to relevant standards made from the following materials may provide suitable chemical protection: PVC, neoprene or nitrile rubber gloves. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, glove thickness, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Use of an apron and over-boots of chemically impervious materials such as neoprene or nitrile rubber is recommended to avoid skin sensitization. The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace. Launder soiled clothes or properly disposed of contaminated material, which cannot be decontaminated.

Appropriate Engineering Controls

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective threshold limit value.

A suitable, NIOSH-approved respirator and goggles should be worn when standing or grinding objects coated with this paint.

Chemical Name	OSHA TWA (ppm)	OSHA TWA (mg/m3)	OSHA STEL (ppm)	OSHA STEL (mg/m3)	OSHA Tables (Z1, Z2, Z3)	OSHA Carcinogen	OSHA Skin designation	ACGIH TWA (ppm)
ACETONE	1000	2400			1			250
ALUMINUM HYDROXIDE								
BUTYL ACETATE	150	710			1			50
ETHYLBENZENE	100	435			1			20
FORMALDEHYDE	0.75 (a)		2 / 15minutes		1,2	1		0.1
METHANOL	200	260			1			200
N-BUTYL ALCOHOL	100	300			1			20
SILICA - PRECIPITATED	20 (b)	80 mg/m3 percent SiO2+2			1,3			
SILICA, AMORPHOUS	20 (b)	80 mg/m3 percent SiO2+2			1,3			
STODDARD	500	2900			1			100

SOLVENT							
TITANIUM DIOXIDE		15			1		
XYLENE	100	435			1		20
ZIRCONIA OXIDE		5			1		

Chemical Name	ACGIH TWA (mg/m3)	ACGIH STEL (ppm)	ACGIH STEL (mg/m3)	ACGIH Carcinogen	ACGIH Notations	ACGIH TLV Basis
ACETONE		500		A4	A4; BEI	URT & eye irr; CNS impair
ALUMINUM HYDROXIDE	1 (R)			A4	A4	Pneumoconiosis; LRT irr; neurotoxicity
BUTYL ACETATE		150				Eye & URT irr
ETHYLBENZENE				A3	OTO;BEI	URT & eye irr; ototoxicity; kidney eff; CNS impair
FORMALDEHYDE		0.3		A1	DSEN; RSEN; A1	URT & eye irr; URT cancer
METHANOL		250			Skin; BEI	Headache; eye dam; dizziness; nausea
N-BUTYL ALCOHOL						Eye & URT irr
SILICA - PRECIPITATED						
SILICA, AMORPHOUS						
STODDARD SOLVENT	[(L)]; [5 (I)];			[A2]; [A4];	[A2]; [A4];	Eye, skin, & kidney dam; nausea; CNS impair
TITANIUM DIOXIDE	0.2 (R)(Nano), 2.5 (R)			A3		LRT irr; pneumoconiosis
XYLENE						Eye irr & URT irr, hemotologic effects; CNS impair
ZIRCONIA OXIDE	5		10	A4	A4	Resp irr

(C) - Ceiling limit, (R) - Respirable fraction, A1 - Confirmed Human Carcinogen, A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans, A4 - Not Classifiable as a Human Carcinogen, BEI - Substances for which there is a Biological Exposure Index or Indices, CNS - Central nervous system, dam - Damage, DSEN - Dermal sensitization, eff - Effects, impair - Impairment, irr - Irritation, LRT - Lower respiratory tract, resp - respiratory, RSEN - Respiratory sensitization, URT - Upper respiratory tract

SECTION 9) PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical Properties

Density	9.91390 lb/gal
% Solids By Weight	57.54380%
% VOC	36.64490%
Density VOC	3.63294 lb/gal
VOC Regulatory	3.93807 lb/gal

Appearance	N/A
Odor Threshold	N/A
Odor Description	N/A
pH	N/A
Water Solubility	N/A
Flammability	N/A
Flash Point Symbol	N/A
Flash Point	N/A
Viscosity	N/A
Lower Explosion Level	N/A
Upper Explosion Level	N/A
Vapor Pressure	N/A
Vapor Density	N/A
Freezing Point	N/A
Melting Point	N/A
Low Boiling Point	N/A
High Boiling Point	N/A
Auto Ignition Temp	N/A
Decomposition Pt	N/A
Evaporation Rate	N/A
Coefficient Water/Oil	N/A

SECTION 10) STABILITY AND REACTIVITY

Chemical Stability

Stable.

Possibility of Hazardous Reactions/Polymerization

No data available.

Conditions To Avoid

Excessive heat.

Incompatible Materials

Strong oxidizers.

Hazardous Decomposition Products

May produce fumes when heated to decomposition.

Fumes may contain carbon monoxide and carbon dioxide.

SECTION 11) TOXICOLOGICAL INFORMATION

Likely route of exposure

Ingestion, Inhalation, Skin absorption

Skin Corrosion/Irritation

Causes skin irritation

0000067-64-1 ACETONE

Can cause skin irritation.

0000071-36-3 N-BUTYL ALCOHOL

Can irritate and burn the skin.

0000123-86-4 BUTYL ACETATE

May cause effects on the central nervous system.

Serious Eye Damage/Irritation

Causes serious eye irritation

0000050-00-0 FORMALDEHYDE

Contact can severely irritate and burn the skin and eyes with possible eye damage.

0000067-56-1 METHANOL

Can irritate the eyes and can cause blurred vision and blindness.

0000067-64-1 ACETONE

Exposure can irritate the eyes.

0000071-36-3 N-BUTYL ALCOHOL

Can irritate and burn the eyes.

0000108-65-6 PROPYLENE GLYCOL MONOMETHYL ETHER ACETATE

Can irritate the eyes.

0000123-86-4 BUTYL ACETATE

Can severely irritate and burn the skin.

Respiratory/Skin Sensitization

Based on available data, the classification criteria are not met.

0000050-00-0 FORMALDEHYDE

Inhaling can irritate the lungs. May cause a skin allergy and an asthma-like allergy.

0000067-56-1 METHANOL

Prolonged or repeated contact can cause a skin rash, dryness, redness and cracking of the skin.

0000067-64-1 ACETONE

Can irritate the nose and throat causing coughing and wheezing.

0000071-36-3 N-BUTYL ALCOHOL

Can irritate the nose, throat and lungs. May cause dryness or cracking.

0000108-65-6 PROPYLENE GLYCOL MONOMETHYL ETHER ACETATE

Can irritate the respiratory tract.

0000123-86-4 BUTYL ACETATE

Can severely irritate and burn the eyes.

Germ Cell Mutagenicity

Based on available data, the classification criteria are not met.

Carcinogenicity

Suspected of causing cancer.

Reproductive Toxicity

Suspected of damaging fertility or the unborn child

0000067-56-1 METHANOL

May be a teratogen in humans since it is a teratogen in animals.

0000123-86-4 BUTYL ACETATE

Can irritate the respiratory tract.

Specific Target Organ Toxicity - Single Exposure

Causes damage to organs

0000050-00-0 FORMALDEHYDE

Exposure can irritate the nose, mouth and throat.

0000067-56-1 METHANOL

May damage the liver, kidneys and nervous system.

0000067-64-1 ACETONE

May affect the kidneys and liver.

0000071-36-3 N-BUTYL ALCOHOL

Exposure can cause headache, dizziness, nausea and vomiting. Can damage the liver and kidneys.

0000108-65-6 PROPYLENE GLYCOL MONOMETHYL ETHER ACETATE

Exposure at high levels could cause depression of the central nervous system. (Short-term exposure).

Specific Target Organ Toxicity - Repeated Exposure

May cause damage to organs through prolonged or repeated exposure.

0000108-65-6 PROPYLENE GLYCOL MONOMETHYL ETHER ACETATE

The substance defats the skin, which may cause dryness or cracking (Repeated exposure).

Aspiration Hazard

Based on available data, the classification criteria are not met.

Acute Toxicity

Toxic in contact with skin

Toxic if inhaled

Toxic if swallowed

0000067-56-1 METHANOL

Inhalation can irritate the nose, throat and lungs causing coughing, wheezing and/or shortness of breath. Can cause nausea, vomiting, diarrhea and abdominal pain. Exposure to high concentrations can cause headache, dizziness, drowsiness, fatigue, loss of consciousness and death. Methanol is readily absorbed by inhalation, ingestion and dermal exposure and is rapidly distributed to tissues according to the distribution of body water.

Likely Routes of Exposure

Inhalation, Ingestion, Skin contact, Eye contact

0000050-00-0 FORMALDEHYDE

The substance can be absorbed into the body by inhalation.

0000067-64-1 ACETONE

Substance can be absorbed into the body by inhalation.

0000071-36-3 N-BUTYL ALCOHOL

Can be absorbed into the body by inhalation of its vapour and by ingestion.

0000108-65-6 PROPYLENE GLYCOL MONOMETHYL ETHER ACETATE

The substance can be absorbed into the body by inhalation of its aerosol or vapour and by ingestion.

Chronic Exposure

0000050-00-0 FORMALDEHYDE

Formaldehyde has caused cancer in test animals at high concentrations (5-15ppm).

Formaldehyde is classified as a Suspected Human Carcinogen (A2) by ACGIH, and as Probably Carcinogenic to Humans (Group 2A) by IARC. Formaldehyde has caused cancer in test animals.

0000100-41-4 ETHYLBENZENE

CARCINOGENIC EFFECTS: Ethyl Benzene has been listed by IARC as Group 2B, Possibly Carcinogenic to Humans.

TERATOGENIC EFFECTS: Ethyl Benzene has been Classified as POSSIBLE for humans.

0001330-20-7 XYLENE

High exposure to Xylenes in some animal studies have been reported to cause health effects on the developing embryo/fetus.

Xylene in high concentrations has caused embryotoxic effects in laboratory animals.

Potential Health Effects - Miscellaneous

0000067-56-1 METHANOL

Increased susceptibility to the effects of this material may be observed in people with preexisting disease of any of the following: eyes, kidneys, liver, skin. Excessive human exposure to methanol may lead to: fatigue, headache, anaesthetic, neurologic effects, and visual difficulties including blindness or death. Recurrent overexposure may result in liver and kidney injury. Has been toxic to the fetus in laboratory animals at doses that are toxic to the mother. Ingestion may cause any of the following: blindness. Eye contact may cause any of the following: conjunctivitis, mild irritation, corneal opacity.

0000067-64-1 ACETONE

The following medical conditions may be aggravated by exposure: lung disease, eye disorders, skin disorders. Overexposure may cause damage to any of the following organs/systems: blood, central nervous system, eyes, kidneys, liver, respiratory system, skin.

0000071-36-3 N-BUTYL ALCOHOL

May cause abnormal blood forming function with anemia. Liquid splashes in the eye may result in chemical burns.

0000100-41-4 ETHYLBENZENE

Is an IARC, NTP or OSHA carcinogen. Increased susceptibility to the effects of this material may be observed in people with preexisting disease of any of the following: central nervous system, kidneys, liver, lungs. Recurrent overexposure may result in liver and kidney injury. Studies in laboratory animals have shown reproductive, embryotoxic and developmental effects. WARNING: This chemical is known to the State of California to cause cancer.

0000108-65-6 PROPYLENE GLYCOL MONOMETHYL ETHER ACETATE

Recurrent overexposure may result in liver and kidney injury.

0000123-86-4 BUTYL ACETATE

May cause abnormal liver function. The following medical conditions may be aggravated by exposure: respiratory system. Tests for embryotoxic activity in animals has been inconclusive. Rats exposed to very high airborne levels have exhibited high frequency hearing deficits. The significance of this to man is unknown. Has been toxic to the fetus in laboratory animals at doses that are toxic to the mother.

0001330-20-7 XYLENE

Increased susceptibility to the effects of this material may be observed in people with preexisting disease of any of the following: bone marrow, cardiovascular system, central nervous system, kidneys, liver, lungs. Recurrent overexposure may result in liver and kidney injury. High exposures may produce irregular heart beats. Canada classifies Xylene as a developmental toxin as high exposures to xylenes in some animal studies have been reported to cause health effects on the developing fetus/embryo. These effects were often at levels toxic to the adult animal. The significance of these effects to humans is not known. Repeated or prolonged skin contact may cause any of the following: irritation, dryness, cracking of the skin.

0013463-67-7 TITANIUM DIOXIDE

Is an IARC, NTP or OSHA carcinogen. In a lifetime inhalation test, lung cancers were found in some rats exposed to 250 mg/m³ respirable titanium dust. Analysis of the titanium dioxide concentrations in the rat's lungs showed that the lung clearance mechanism was overwhelmed and that the results at the massive 250 mg/m³ level are not relevant to the workplace. Results of a DuPont epidemiology study showed that employees who had been exposed to Titanium Dioxide were at no greater risk of developing lung cancer than were employees who had not been exposed to Titanium dioxide. No pulmonary fibrosis was found in any of the employees and no association was observed between Titanium dioxide exposure and chronic respiratory disease or x-ray abnormalities. Based on the results of this study DuPont concludes that titanium dioxide will not cause lung cancer or chronic respiratory disease in humans at concentrations experienced in the workplace.

0000050-00-0 FORMALDEHYDE

LC50 (rat): 8000 ppm (4-hour exposure) (24)

LD50 (oral, male rat): 2500 mg/kg (25)

LD50 (oral, rat): 2920 mg/kg (26)

LD50 (dermal, guinea pig): greater than 15000 mg/kg (cited as greater than 0.94 mL/kg) (27)

LD50 (dermal, rat): 5070 mg/kg (28, unconfirmed)

0000067-56-1 METHANOL

LC50 (rat): 64000 ppm (4-hour exposure) (14, unconfirmed)

LD50 (oral, rat): 5628 mg/kg (14, unconfirmed)

LD50 (oral, 14-day old rat): 5850 mg/kg (cited as 7.4 mL/kg) (15)

LD50 (oral, young adult rat): 10280 mg/kg (cited as 13.0 mL/kg) (15)

LD50 (oral, monkey): 3000 mg/kg (1/1 animal died) (16) LD50 (dermal, rabbit): 15800 mg/kg (cited as 20 mL/kg) (17 citing unpublished information)

0000067-64-1 ACETONE

LC50 (male rat): 30000 ppm (4-hour exposure); cited as 71000 mg/m³ (4-hour exposure) (29)

LC50 (male mouse): 18600 ppm (4-hour exposure); cited as 44000 mg/m³ (4-hour exposure) (29)

LD50 (oral, female rat): 5800 mg/kg (24)

LD50 (oral, mature rat): 6700 mg/kg (cited as 8.5 mL/kg) (31)

LD50 (oral, newborn rat): 1750 mg/kg (cited as 2.2 mL/kg) (31)

LD50 (oral, mouse): 3000 mg/kg (32, unconfirmed)

LD50 (dermal, rabbit): Greater than 16000 mg/kg cited as 20 mL/kg) (30)

0000071-36-3 N-BUTYL ALCOHOL

LC50 (rat): greater than 8000 ppm (4-hour exposure) (14)

LD50 (oral, rat): 2510 mg/kg (15)

LD50 (oral, male rat): 790 mg/kg (16)*

LD50 (oral, female rat): 2020 mg/kg (16)* *(Note: the rats used in this study appear to have been very young (60-100 grams).)

LD50 (oral, hamster): 1200 mg/kg (11, original)

0000100-41-4 ETHYLBENZENE

LC50 (inhalation, rat): 4000 ppm; 4-hour exposure (3)

LD50 (oral, rat): 3.5 g/kg (1,3,5,10)

LD50 (oral, rat): 4.72 g/kg (3,5,7,8)

LD50 (dermal, rabbit): 17.8 g/kg (11)

0000123-86-4 BUTYL ACETATE

LC50 (rat): 1802 mg/m3; 4-hour exposure (aerosol)(9) Note: A lower LC50 (aerosol) value of 760 mg/m3 (160 ppm); 4-hour exposure has been reported.(11,27) Extensive research has failed to confirm this value.

LD50 (oral, rat): 10770 mg/kg (12, unconfirmed)

LD50 (oral, mouse): 7100 mg/kg (5)

LD50 (oral, rabbit): 7400 mg/kg (cited as 64 millimols/kg) (13)

LD50 (dermal, rabbit): Greater than 5000 mg/kg (3, unconfirmed)

0001330-20-7 XYLENE

LC50 (rat): 6350 ppm (4-hour exposure) (unspecified isomers and ethylbenzene) (1)LC50 (rat): 6700 ppm (4-hour exposure) (65% m-xylene, 7.6% o-xylene, 7.8% p-xylene, 19.3% ethylbenzene) (2) ethylbenzene) (1)

LC50 (rat): 6700 ppm (4-hour exposure) (65% m-xylene, 7.6% o-xylene, 7.8% p-xylene, 19.3% ethylbenzene)(2)

LD50 (oral, rat): 5400 mg/kg (52% m-, 19% o-, 24% p-) (1)LD50 (oral, female mouse): 5251 mg/kg (60.2% m-, 9.1% o-, 14.6% p-, 17.0% ethylbenzene) (4)

LD50 (oral, male mouse): 5627 mg/kg (60.2% m-, 9.1% o-, 14.6% p-, 17.0% ethylbenzene) (4)

LD50 (dermal, rabbit): 12180 mg/kg (m-xylene); greater than 1700 mg/kg (mixed xylenes - undefined composition) (3)

LD50 (oral, female mouse): 5251 mg/kg (60.2% m-, 9.1% o-, 14.6% p-, 17.0% ethylbenzene) (4)

LD50 (oral, male mouse): 5627 mg/kg (60.2% m-, 9.1% o-, 14.6% p-, 17.0% ethylbenzene) (4)

LD50 (dermal, rabbit): 12180 mg/kg (m-xylene); greater than 1700 mg/kg (mixed xylenes - undefined composition) (3)

0008052-41-3 STODDARD SOLVENT

LC50 (rat): greater than 5500 mg/m3 (880 ppm) (whole body exposure for 4 hours) (1)

LC50 (rat): greater than 8200 mg/m3 (1300 ppm) (2)

LD50 (oral, rat): greater than 5 g/kg (1)

LD50 (dermal, rabbit): greater than 3 g/kg (1)

0013463-67-7 TITANIUM DIOXIDE

LC50 (inhalation, Rat): >5.09 mg/L ; 4-hr exposure

Test atmosphere: dust/mist

No mortality observed at this dose.

LD50 Rat: > 5000 mg/kg

LD50 Hamster: > 10000 mg/kg

SECTION 12) ECOLOGICAL INFORMATION

Toxicity

Harmful to aquatic life

Harmful to aquatic life with long lasting effects

0000123-86-4 BUTYL ACETATE

Readily biodegradable

Persistence and Degradability

0000067-56-1 METHANOL

72% aerobic biodegradability.

Readily biodegradable.

0000067-64-1 ACETONE

91% readily biodegradable, Method: OECD Test Guideline 301B

Readily biodegradable.

0000071-36-3 N-BUTYL ALCOHOL

Readily biodegradable.

0000108-65-6 PROPYLENE GLYCOL MONOMETHYL ETHER ACETATE

Readily biodegradable.

0000123-86-4 BUTYL ACETATE

Readily biodegradable

0001330-20-7 XYLENE

50% of applied radiolabelled o-xylene was mineralised in 23 days, and 50% p-xylene was mineralised in 13 days.

0025265-71-8 DIPROPYLENE GLYCOL

Biodegradable.

Bioaccumulative Potential

0000108-65-6 PROPYLENE GLYCOL MONOMETHYL ETHER ACETATE

Substance has a low potential for bioaccumulation, Log Kow < 1.

Substance has a low potential for bioaccumulation, Log Kow = 1.2.

0025265-71-8 DIPROPYLENE GLYCOL

Bioaccumulation is not expected.

Mobility in Soil

0000067-56-1 METHANOL

Will not adsorb on soil.

0000067-64-1 ACETONE

The substance is not PBT / vPvB.

Other Adverse Effects

No data available.

Results of the PBT and vPvB assessment

0000067-56-1 METHANOL

The substance is not PBT / vPvB.

0000071-36-3 N-BUTYL ALCOHOL

The substance is not PBT / vPvB.

0000108-65-6 PROPYLENE GLYCOL MONOMETHYL ETHER ACETATE

The substance is not PBT / vPvB.

0000123-86-4 BUTYL ACETATE

The substance is not PBT / vPvB.

SECTION 13) DISPOSAL CONSIDERATIONS

Waste Disposal

Under RCRA it is the responsibility of the user of the product to determine at the time of disposal whether the product meets RCRA criteria for hazardous waste. Waste management should be in full compliance with federal, state and local laws.

Empty Containers retain product residue which may exhibit hazards of material, therefore do not pressurize, cut, glaze, weld or use for any other purposes. Return drums to reclamation centers for proper cleaning and reuse.

SECTION 14) TRANSPORT INFORMATION

U.S. DOT Information

Proper Shipping Name: PAINT
Identification Number : UN/NA 1263
Hazard Class:3
Packing group: II

IMDG Information

Proper Shipping Name: PAINT
Identification Number : UN/NA 1263
Hazard Class:3
Packing group: II

IATA Information

Proper Shipping Name: PAINT
 Identification Number : UN/NA 1263
 Hazard Class:3
 Packing group: II

SECTION 15) REGULATORY INFORMATION**REGULATORY INFORMATION**

TSCA Inventory: All components of this product are in compliance with U.S. TSCA Chemical Substance Inventory Requirements.

Canada Domestic Substances List: All components of this product are listed on the Domestic Substances List

CAS	Chemical Name	% By Weight	Regulation List
0013463-67-7	TITANIUM DIOXIDE	17% - 28%	DSL, SARA312, CA_Carcinogen
0000067-56-1	METHANOL	11% - 26%	SARA313, Canada_NPRI, DSL, HAPS, SARA312, WI_NR438 - WI_NR438 - AIR CONTAMINANT EMISSION INVENTORY REPORTING REQUIREMENTS
NA-Repcolite	ALKYD RESIN	9% - 21%	SARA312
0001330-20-7	XYLENE	5% - 11%	SARA313, Canada_NPRI, DSL, HAPS, SARA312, WI_NR438 - WI_NR438 - AIR CONTAMINANT EMISSION INVENTORY REPORTING REQUIREMENTS
0068002-19-7	Urea, polymer with formaldehyde, butylated	4% - 10%	DSL, SARA312
0000123-86-4	BUTYL ACETATE	3% - 8%	Canada_NPRI, DSL, SARA312, WI_NR438 - WI_NR438 - AIR CONTAMINANT EMISSION INVENTORY REPORTING REQUIREMENTS
0000067-64-1	ACETONE	3% - 7%	DSL, SARA312, WI_NR438 - WI_NR438 - AIR CONTAMINANT EMISSION INVENTORY REPORTING REQUIREMENTS
NA-Repcolite	MELAMINE RESIN	2.0% - 5%	SARA312
0112926-00-8	SILICA - PRECIPITATED	1.6% - 4%	DSL, SARA312
0009004-36-8	CELLULOSE ACETATE BUTYRATE	1.4% - 3%	DSL, SARA312
0000108-65-6	PROPYLENE GLYCOL MONOMETHYL ETHER ACETATE	1.3% - 3%	Canada_NPRI, DSL, SARA312
0007631-86-9	SILICA, AMORPHOUS	0.2% - 4%	DSL, SARA312
0000100-41-4	ETHYLBENZENE	0.2% - 4%	SARA313, Canada_NPRI, DSL, HAPS, SARA312, CA_Carcinogen, WI_NR438 - WI_NR438 - AIR CONTAMINANT EMISSION INVENTORY REPORTING REQUIREMENTS
0021645-51-2	ALUMINUM HYDROXIDE	0.1% - 2%	DSL, SARA312
0001314-23-4	ZIRCONIA OXIDE	0.0% - 0.5%	DSL, SARA312, WI_NR438 - WI_NR438 - AIR CONTAMINANT EMISSION INVENTORY REPORTING REQUIREMENTS
0000071-36-3	N-BUTYL ALCOHOL	0.0% - 0.4%	SARA313, Canada_NPRI, DSL, SARA312, WI_NR438 - WI_NR438 - AIR CONTAMINANT EMISSION INVENTORY REPORTING REQUIREMENTS
0009002-88-4	POLYETHYLENE	0.0% - 0.4%	DSL, SARA312
0025265-71-8	DIPROPYLENE GLYCOL	Trace	DSL, SARA312
0008052-41-3	STODDARD SOLVENT	Trace	Canada_NPRI, DSL, SARA312, WI_NR438 - WI_NR438 - AIR CONTAMINANT EMISSION INVENTORY REPORTING REQUIREMENTS
0000050-00-0	FORMALDEHYDE	Trace	SARA313, Canada_NPRI, DSL, HAPS, SARA312, CA_TAC_Carcinogen, CA_Carcinogen, WI_NR438 - WI_NR438 - AIR CONTAMINANT EMISSION INVENTORY REPORTING REQUIREMENTS
0070657-70-4	2-METHOXY-1-PROPANOL ACETATE	Trace	Canada_NPRI, DSL, SARA312

The information in this Section does not list non-hazardous components that might have relevant SARA312 regulatory values, if they are present at less than 1%. Please contact

manufacturer for more information.



WARNING:This product can expose you to chemicals including TITANIUM DIOXIDE, which is known to the State of California to cause cancer, and METHANOL, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

SECTION 16) OTHER INFORMATION

General

ACGIH- American Conference of Governmental Industrial Hygienists; ANSI- American National Standards Institute; Canadian TDG- Canadian Transportation of Dangerous Goods; CAS- Chemical Abstract Service; Chemtrec- Chemical Transportation Emergency Center (US); CHIP- Chemical Hazard Information and Packaging; DSL- Domestic Substances List; EC- Equivalent Concentration; EH40 (UK)- HSE Guidance Note EH40 Occupational Exposure Limits; EPCRA- Emergency Planning and Community Right-To-Know Act; ESL- Effects screening levels; HMIS- Hazardous Material Information Service; LC- Lethal Concentration; LD- Lethal Dose; NFPA- National Fire Protection Association; OEL- Occupational Exposure Limits; OSHA- Occupational Safety and Health Administration, US Department of Labor; PEL- Permissible Exposure Limit; SARA (Title III)- Superfund Amendments and Reauthorization Act; SARA 313- Superfund Amendments and Reauthorization Act, Section 313; SCBA- Self-Contained Breathing Apparatus; STEL- Short Term Exposure Limit; TCEQ- Texas Commission on Environmental Quality; TLV- Threshold Limit Value; TSCA- Toxic Substances Control Act Public Law 94-469; TWA- Time Weighted Value; US DOT- US Department of Transportation; WHMIS- Workplace Hazardous Materials Information System.

HMIS

Health	/ 2
FLAMMABILITY	3
Physical Hazard	0
Personal Protection	X

(*) - Chronic effects

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks

Version 5.0:

Revision Date: Jan 31, 2024

DISCLAIMER

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist. The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.