

DESCRIPTION and USES

This product is a professional quality interior latex flat paint that features good hiding, washability, easy no-spatter application and good touch-up. This paint is ideal for use on drywall, plaster and masonry in residential and commercial construction. It can be used as a paint and primer all in one, but in certain situations the use of a primer is recommended to achieve maximum performance.

SURFACE PREPARATION

All surfaces to be primed must be dry and free of dust and dirt, oil or other contamination. Loose and peeling paint must be removed to provide a sound surface. Patching and caulking should be done prior to painting. Prime all unpainted surfaces if necessary with a suitable primer.

APPLICATION

Apply with synthetic bristle brush, roller or airless spray. For airless spray, use .015 - .017 tip adjusting pressure as needed. Back rolling after spray application is recommended. Some surfaces may require two coats to achieve a uniform appearance. Allow at least two hours of dry time between coats. For best results apply at a maximum spread rate of 400 square feet per gallon. Do not apply at temperatures below 55°F.

SAFETY INFORMATION

For complete safety information, refer to the SAFETY DATA SHEET (SDS) for this product.

COLORS

White, all RepcoLite Color Renaissance colors and any custom color.

The suggestions for use and technical data here given are accurate to the best of our knowledge and are offered in good faith. Because the conditions and use of our products are beyond our control, our liability, if any, is limited to the replacement of defective material only. RepcoLite Paints, Inc. DISCLAIMS ALL OTHER WARRANTIES relating to our products and DISCLAIMS ALL WARRANTIES RELATING TO THEIR APPLICATION, expressed or implied, INCLUDING but not limited to warranties of merchantability and fitness for a particular purpose. TECHNICAL DATA IS SUBJECT TO CHANGE WITHOUT NOTICE.

TECHNICAL DATA

Vehicle Type:	Vinyl Acrylic Latex
Density:	11.1 lb/gal
Weight Solids:	48.1%
Volume Solids:	30.9%
Coverage:	300 – 400 SF/Gallon depending on surface porosity
Dry Time:	
<i>Touch:</i>	30 Minutes
<i>Recoat:</i>	2 Hours
	Allow additional dry time in humid conditions
Primer:	
<i>Drywall:</i>	44310 ELEMENTS Latex Wall Primer 44410 Quick Seal
<i>Plaster:</i>	44110 Prime-All 44313 Quick Sand
<i>Masonry:</i>	44610 Block Filler
<i>Wood:</i>	44110 Prime-All 44010 Pro Flo Primer Undercoater
<i>Steel:</i>	44917 Metl-Clad Gray Metal Primer
VOC:	131 g/l
Clean Up:	Water

PRODUCT CODE INFORMATION

42410	ELEMENTS Latex Eggshell White
42403	ELEMENTS Latex Eggshell #703 base
42406	ELEMENTS Latex Eggshell #706 base