

DESCRIPTION AND USES

Mira-Spar Exterior Varnish is a premium quality clear finish that resists the harmful effects of wind, rain, sun, and temperature extremes. A combination of tough plastic resins, linseed oil, tung oil, and ultra-violet resistors provides maximum protection from the elements. This varnish is suitable for use on picnic tables, patio furniture, and exterior woodwork. Mira-Spar Exterior Varnish is available in a high gloss as well as a soft gloss finish.

SPECIFICATIONS

SURFACE PREPARATION: All wood surfaces to be finished must be clean, dry and free of contaminants such as oil or wax. Moisture content of wood should be 7-9%. Sand all rough or previously finished surfaces with 120 - 150 grit sandpaper. Use a tack cloth to insure a dust-free surface.

APPLICATION: Apply with a clean brush, pad applicator, or spray. Apply two coats to bare or stained wood, sanding lightly between coats to smooth the surface. Apply 1 or 2 coats as needed to previously finished wood. To insure intercoat adhesion, always sand lightly between coats. Allow to dry 24 hours before subjecting finish to traffic or wear. Do not apply at temperatures below 60°F. Thinning this product will bring it out of compliance with current VOC regulations. Do NOT THIN. DO NOT use this product over shellac or sanding sealers that contain zinc stearate.

CLEAN UP: Use Paint Thinner (Mineral Spirits).

PRECAUTIONS

NOTICE: Reports have associated repeated and prolonged occupational exposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

For complete safety information, refer to the MATERIAL SAFETY DATA SHEET for this product.

COMPANION PRODUCTS

- 760 Series Products

PRODUCT CODES

- 764C - Clear Soft Gloss
- 769C - Clear Gloss

TECHNICAL DATA

VEHICLE TYPE: Linseed/Tung Oil

VOLUME SOLIDS: 45%

WEIGHT SOLIDS: 52%

DENSITY: 7.6 lbs/gal

ACTUAL VOC: 3.58 lbs/gal

REGULATORY VOC: 430 g/L

SEALER: Self-seal

CLEAN UP SOLVENT: Mineral Spirits

COVERAGE: 450 - 500 square feet at 1 mil dry film thickness.

DRY TIME: Dry to touch in 4-6 hours. Sand or re-coat in 12-16 hours.

SHELF LIFE: 1 year shelf life when properly stored.

For complete safety information, refer to the SAFETY DATA SHEET for this product.



RepcoLite Paints, Inc.
473 W. 17th St.
Holland, MI 49423
(616) 396-1275
www.repcolite.com